


INSTALLATION INSTRUCTIONS: DRL BLACKOUT Kit for Toyota Vehicles

LED Daytime Running Light Kit [mounts in factory fog lamp openings]

KIT CONTENTS: 2 LED DRL Lamp Assembly; Bumper Mount Bezels; ECM Driver Box; Harness Bag w/Switch

1. Disconnect negative battery cable
2. From front of vehicle, run the DRL *Wire Harness* on the driver side from the lower grille towards the firewall. Wire tie as needed
3. Locate large vehicle harness grommet on driver side firewall. If accessible, cut the auxiliary wiring access nipple, or cut ¼" slit. Carefully push the RED, BLACK, RED/WHITE & BLACK/WHITE wires through firewall. Do not damage pin connectors. Seal with RTV Silicone (picture 1)



Picture 1

4. Prepare a dash switch knockout for installation of the DRL switch (picture 2)



Picture 2

5. Inside the cabin, remove lower dash panel for access. Locate wires pushed through in step 3, at the grommet above the gas pedal.
6. Route the wire harness to reach the lower part of the steering column
7. Push the pins into plug connectors. Make certain wire colors on the connectors align with the wire colors on the ECM driver box sockets ~ black to black, red to red (picture 3)



Picture 3

8. Connect *ECM Driver Box* to the wires pushed into the connectors on step 7 (*make sure wire colors are aligned*).
9. Secure the driver box next to the steering wheel column with 14in wire tie
10. Route the wires through the steering column. Wire tie as needed
11. T-tap the RED wire from DRL harness to a +12V *ignition switched* wire.
12. T-tap the BLUE signal wire from DRL harness to +12V *parking lamp wire* or *dash illumination circuit*.
13. Secure BLACK wire to -12V *ground*
14. Plug in the switch. Secure any excess wire, the relay and fuse with wire ties
15. Reinstall dash panels and connectors
16. On the driver side, route the DRL wires under car to reach left fog light area.
17. Remove lower splash shields on both sides as needed for access.
18. Remove plastic fog light cover panels
19. Install *DRL Lamp Assembly* into bumper with screws and existing tabs
20. Connect plug to left side DRL Lamp
21. Run right side of wire harness under skid plate and secure with wire ties, and Connect plug to right side DRL Lamp
22. Snap on both DRL bezels
23. Reattach the lower splash shields
24. Reinstall negative battery cable
25. **TEST DRL OPERATION:**
 - Full power with ignition & DRL switch on
 - Dimmed with headlights turned on
 - Off with switch disarmed



DONMAR
SUNROOFS & ACCESSORIES
<http://www.donmar.com>