



OE Fit Fog Light Kit Instructions: TPR-412 2012~ Toyota Prius Original

1. Disconnect negative battery cable
2. Remove the radiator support opening cover, (use protective tape around the bumper)
3. Remove left and right splash shields from the front of the car.
4. On the left side of bumper, disconnect the turn signal connector, then remove bumper from vehicle [Picture 1]



Picture 1



Picture 2


5. Remove the secondary splash shield from bumper. Remove two screws and then disengage clips. [Picture 2]
6. Remove factory lower radiator grill from bumper: there are two retainers on the outside and 20 claws. [Picture 2]
7. Mount fog lights into replacement lower grill by sliding fog light tabs into slots and secure other side with supplied screw
8. Install supplied lower grill to bumper
9. Connect the **BLACK** wire from fog light harness to -12v floating body ground
10. Run the **RED** fog light harness wire through the firewall to the inside the fuse block. Follow the path of the big white wire. Connect this wire to a 15A ignition switched circuit in the fuse box.
11. Run the fog light harness to inside of cabin.
12. Connect fog lights and reinstall lower radiator grill, splash shields and bumper (reconnect turn signal wire harness)
13. Remove dash panels
14. Run fog light harness on the driver side of car. Use wire ties as needed.
15. Mount switch into dash knockout
16. T-Tap **ORANGE/BLACK** wire [low beam interlock] from fog light harness to connector 2C pin 32, green wire. Pin 32 is the headlight relay wire and is on the left side of the connector 7th pin up from bottom of the connector. Connector 2C located left of the steering column above big white wire [Picture 3 & 4]
17. T-Tap **GREEN/BLACK** wire [high beam interlock] from fog light harness to connector 2C pin 22, yellow wire which is the DIM relay wire. [Picture 1 & 2].
18. Reconnect negative battery cable and TEST fog lamp operation. They should function only while low beams are turned on, and will be forced off when high beams are on.

OE Fit Fog Light Kit Instructions: TPR-412 2012~ Toyota Prius Original



Picture 3

IMPORTANT NOTE: This kit is wired for Negative pin trigger on both relays. Orange/Black & Green/Black signal wires should NOT connect to +12V or you may damage the relays and harness.



Picture 4: Pin side view

19. Reinstall all removed panels inside and outside.
20. Re-Verify fog lamp operation.
21. Cleanup and deliver vehicle

DONMAR
SUNROOFS & ACCESSORIES
<http://www.donmar.com>