DONMAR SKYROOF® Spoiler Sunroof Warranty

LIMITED THREE YEAR WARRANTY

DONMAR Enterprises, Inc. warrants SKYROOF Spoiler Sunroofs against defective materials and workmanship, while under normal use and service, to the original purchaser, for three (3) years from the date of installation. This warranty is not transferrable. The sunroof must be properly installed by an Authorized Professional Installation Center. EXCEPTION: No vandalism or glass breakage will be covered. No other express or implied warranties are given and this warranty is limited as follows:

In the event any covered defect is discovered, the owner must, at his/her own expense, bring the vehicle to the original installer, or nearest DONMAR Authorized Installation Center for correction. DONMAR will repair or replace (at our option) parts found to be defective and subject to such warranty coverage, provided that they were not damaged by alteration, improper use or application, or neglect. It is the responsibility of the installation center to perform all warranty

This warranty does not apply to any DONMAR product which has been subject to: abuse, misuse, improper use, installation or application, negligence, neglect, accident, flood, fire, or acts of God, nor does it cover loss of time, inconvenience, use of the vehicle, or any other indirect or consequential damages. This warranty is void if repairs have been made or attempted by unauthorized parties. Under no circumstances will labor or installation charges be reimbursed by DONMAR.

NO OTHÉR EXPRESSED OR IMPLIED WARRANTIES ARE GIVEN INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

Warranty coverage requires proof of installation date with the original warranty card and/or installation bill of sale.





7980 Bayberry Road • Jacksonville, Florida 32256 • 904/731-3393 • www.donmar.com

form SkyroofLS-WtyCard.pmd 8/05

Keep this warranty card with all of your important vehicle records.

Notwithstanding anything contained in this warranty or in any other material related to SKYROOF Sunroofs to the contrary, DONMAR's liability on defective merchandise is limited to repair or replacement of items found to be defective (subject to inspection), and DONMAR shall in no event be liable for any incidental or other damages as a result of any such defect.

Owner may be subject to labor charges if repaired by other than the original installation center. Under no circumstances will labor or installation charges be reimbursed by DONMAR.

It shall be the responsibility of the installer to determine suitability for each application. The installer shall assume all risks and liability in connection with the sunroof installation.

IMPORTANT WARRANTY INFORMATION					
SKYROOF® Model:	☐ LS (rollo)	LSS (sliding shade)	VIN:		
Vehicle Make		Model		Year	
Vehicle Owner					
Address					
City		State		Phone ()
Installation Center				Phone ()
Installer Signature			Ins	stall Date	

SKYROOF® Spoiler Sunroof Operation & Maintenance

SUNROOF OPERATION

TO OPEN GLASS: Press and hold the open arrow on the switch until the glass panel reaches the desired postion, then release the switch. Panel may be stopped in any position from partial vent to full open.

TO CLOSE GLASS: Press and hold the close arrow on the switch until the glass panel reaches the desired postion, then release the switch.

NOTE: Do not hold the switch more than 5 seconds after reaching full open or closed postion to avoid damaging the motor and drive system.



















SUNROOF MAINTENANCE

GASKET: Clean the gasket at least twice a year with a clean, damp, lint free cloth, If the seal is very dirty, wipe with a mild detergent solution, then wipe off with clean a damp cloth. NEVER apply mineral oil, petroleum ielly or vinyl dressing to your gasket. If the seal is very dry, apply a thin coating of light silicone lubricant spray.

GLASS: Clean the glass panel with a non-ammonia glass cleaner and lint free cloth. Hard water spots can can be removed with household white vinegar.

FRAME: The outer main frame is aluminum, coated with a baked-on textured finish. It should be cleaned regularly with a mild detergent solution. Do not apply wax or dressing to the textured finish as it will cause a white chalky buildup [can be removed with a soft brush and mild detergent].

DRIVE MECHANISM: Dirt, grit, salt and debris can cause your sunroof to open or close sluggishly and may cause wear or even failure over time. Make sure your tracks are clean and clear of debris, dirt, etc. Inspect the tracks and remove any debris or dirt by hand, followed by gently wiping with a soft lint-free cloth until the surface is clean. Clean and apply white lithium grease annually to maintain smooth operation.

Your local DONMAR Dealer can clean your sunroof, inspect and adjust the drive, and gasket and send you on your way in no time at all.

SKYROOF® and DONMAR® are registered trademarks of DONMAR Enterprises, Inc., U.S.A.